

**SAFETY DATA SHEET**  
**IN ACCORDANCE WITH REGULATION (EC) 1907/2006 (REACH)**  
**Contact Cleaner**

Preparing date: 18 June 2024

Version: 1

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier: Contact Cleaner**

UFI: 7FNA-TF99-HSKV-FF5E

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

**Identified uses:** Maintenance.  
For consumer, industrial and professional use.  
**Uses advised against:** Other than above.

**1.3 Details of the supplier of the safety data sheet:**

**Distributor:**

SZAKAL MET-AL Zrt  
2040 Budaörs, Kamaraerdei  
u 9/C.

~~Tel.: +36 23 431-000~~

**Email address for a  
competent person  
responsible for the safety  
data sheet:**

HUNGARY

kozpont@szakalmetal.hu

**1.4 Emergency telephone number:**

Health Toxicological Information Service, Hungary:  
06 1 476 6464 (available day and night)

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture:  
in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aerosols Category 1 H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
Serious eye damage/eye irritation Category 2 H319 Causes serious eye irritation.  
Acute toxicity Category 4 H332 Harmful if inhaled.  
Specific target organ toxicity – single exposure Category 3  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
Hazardous to the aquatic environment (chronic) Category 3  
H412 Harmful to aquatic life with long lasting effects.



## 2.2 Label elements:

**Components:** <25% Hydrocarbons, C6-C7, isoalkanes, ring compounds  
25% denatured alcohol, 50% propane/butane/isobutane



**Danger**

GHS02...



GHS07

### Hazard Statement(s):

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary Statement(s):

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container to: As hazardous waste.

## 2.3 Other hazards:

Results of the PBT and vPvB assessment: Does not comply with PBT or vPvB substances relevant criteria.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures:**

Identifier	CAS Number	EC Number	Index Number/ REACH Registration Number	Concentration by weight	Classification in accordance with Regulation (EC) No 1272/2008
Hydrocarbons, C6-C7, isoalkanes, cyclics (Special petrol 80/110)	-	926-605-8	-/ 01- 2119486291- 36-0003	approx. 25 %	* Flam. Liq. 2 H225 Asp. Tox. 1 H304 STOT SE 3 H336 Aquatic Chronic 2 H411
Contain: < 3% n-hexane	110-54-3	203-777-6	601-037-00-0/ -		* Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 Repr. 2 H361f STOT SE 3 H336 STOT RE 2 H373 Aquatic Chronic 2 H411
Denatured alcohol (ethyl alcohol ≥92.0 vol%, isopropyl alcohol 2.0% tert- butanol 1.0% denatonium benzoate 1.001%)	64-17-5	200-578-6	603-002-00-5/ -	approx. 25 %	* Flam. Liq. 2 H225 Eye Irrit. 2 H319 Acute Tox. 4 H332 STOT SE 3 H335, H336
Propellant – PB 4.2 T:				approx. 50 %	
Propane	74-98-6	200-827-9	601-003-00-5/ 01-2119486944- 21	-	Flam. Gas 1 H220 Press. Gas (liquefied gas)
Butane	106-97-8	203-448-7	601-004-00-0/ 01-2119474691- 32	-	Flam. Gas 1 H220 Press. Gas (liquefied gas)
Isobutane	75-28-5	200-857-2	601-004-00-0/ 01-2119485395- 27-0019	-	Flam. Gas 1 H220 Press. Gas (liquefied gas) Muta. 1B H340 Carc. 1A H350
(1,3-butadiene content: < 0.1%)	106-99-0	203-450-8	601-013-00-X/ 01-2119471988- 16		

\* Classification given by the manufacturer.

For the full text of H-sentences mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures:

Inhalation: (applies to propellant gas) The injured person must be taken to fresh air and kept at rest. In the event of respiratory irritation (cough) or difficulty breathing, call a doctor immediately. If breathing has stopped, a qualified person should start artificial respiration, or if the heart has stopped, cardiopulmonary resuscitation. Giving oxygen can have a beneficial effect if it is given by a qualified person, preferably on medical advice.

Skin contact: (applies to propellant) Clothing contaminated with the product must be removed immediately. The affected skin surface should be washed with lukewarm water and soap. Do not attempt to rewarm the affected skin on the spot. Do not rub or apply dry heat. Carefully cut around the part of the cloth that adheres to the wound. Cover the casualty loosely with a sterile dressing. Get the injured person to a first aid station or hospital quickly.

Eye contact: (applies to propellant gas) The eyes must be thoroughly rinsed with plenty of running water for at least 15 minutes (while pulling the eyelids apart). You need to remove the contact lenses, if you have them, and this is easy to do. Do not attempt to overheat. Cover both eyes with a sterile cloth then the eye should be shown to a doctor.

Ingestion: (spray) The product is sold in an aerosol bottle, so it is unlikely to be swallowed. In case of accidental ingestion, the victim should not be induced to vomit, a doctor should be consulted.

### 4.2 Most important symptoms and effects, both acute and delayed:

Information on denatured alcohol: If alcohol is inhaled or swallowed, coughing, headache, dizziness, drowsiness, stupor, and loss of consciousness may occur.

In case of eye contact: redness, pain, burning sensation.

Propellant gas: In high concentrations, it has a suffocating effect, the lack of oxygen has fatal consequences.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Show the safety data sheet or label to the doctor if possible.

There is no specific antidote.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media:

Suitable extinguishing media: Extinguishing powder, carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, water spray.

Inappropriate extinguishing media: Strong water jet (can only be used to cool the bottle).

### 5.2 Special hazards arising from the substance or mixture:

The area must be evacuated. The fire must only be extinguished from a safe distance or from a protected place. Avoid inhalation of hazardous vapours and toxic decomposition products (approach from the windward side). Due to the aerosol packaging, it is unlikely that a large amount of the mixture will leak out. The heat from the fire can cause a rapid increase in pressure inside the cylinder and cause the cylinder to explode. Personnel and materials not yet reached by the fire must be moved to safety.

Hazardous combustion products: In case of fire, toxic gases may be released: CO, CO<sub>2</sub>, hydrocarbons, aldehydes, carbon black.

### 5.3 Advice for firefighters:

Full fireproof protective equipment. In case of fire, a self-contained breathing apparatus must be worn.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:**

For non-emergency personnel:

Unauthorized persons must be kept away.

Ignition sources must be removed.

Adequate ventilation must be ensured.

Avoid contact with skin or eyes.

The vapour/spray of the product must not be inhaled.

Full protective equipment and a self-contained breathing apparatus must be worn.

Caution, there is a risk of explosion if the leaking material enters the sewer system. In the event of a large spill, the competent authorities must be notified.

For emergency responders:

Unauthorized persons must be kept away.

Ignition sources must be removed.

Adequate ventilation must be ensured.

Avoid contact with skin or eyes.

The vapour/spray of the product must not be inhaled.

Full protective equipment and a self-contained breathing apparatus must be worn.

Caution, there is a risk of explosion if the leaking material enters the sewer system. In the event of a large spill, the competent authorities must be notified.

**6.2 Environmental precautions:**

The product must not be discharged into the sewer or the waters.

Due to the small aerosol packaging, leakage of a large amount is unlikely.

If the spilled material (propellant gas) gets into the sewer network, there is a risk of explosion.

All deeper and more distant sources of ignition must be eliminated.

**6.3 Methods and material for containment and cleaning up:**

Stop the leak if it is safe to do so.

Use a water spray to reduce the concentration of the gas.

Seal off the area until the gas dissipates.

It must be disposed of in accordance with the regulations.

Only non-sparking devices may be used.

Liquid residues must be picked up with an absorbent non-combustible material (dry earth, sand, etc.) and collected until disposal.

**6.4 Reference to other sections:**

Individual protection measures, such as personal protective equipment: see Section 8.

Waste treatment, disposal: see Section 13.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling:**

It can only be used in a well-ventilated area! Keep away from heat and sources of ignition. The rules for pressurized containers must be observed. Avoid inhaling the spray of the mixture, getting it on the skin, getting it in the eyes, and swallowing it.

Use a spark-proof ventilation system, explosion-proof equipment and an intrinsically safe electrical system.

Always shake thoroughly before use.

Risk of fire and explosion: The engine must be stopped, the ignition must be switched off.

There is overpressure in the device. Do not open, knock, puncture, expose to temperatures above 50°C, sunlight, radiant heat or throw into fire, even when empty! Do not spray on an open flame or glowing material. Refilling the device is prohibited!

No smoking!

## 7.2 Conditions for safe storage, including any incompatibilities:

Individual storage requirements: Ensure adequate ventilation.

Electrostatic charging must be prevented.

It should be stored in a dry, cool place at a temperature below 35°C.

Keep away from heat and sources of ignition.

Keep away from children and separate from food!

Hands should not be wiped with a rag that was previously used for cleaning. Soaked rags should not be placed in the pockets of work clothes.

Incompatible materials: Strong acids, oxidizing agents.

Packaging material:

Data for denatured alcohol:

Suitable for: stainless steel, carbon steel, glass, ceramic, polypropylene, titanium, cast bronze, cast iron.

Not suitable: natural rubber, PVC, methyl methacrylate plastic, zinc, copper, aluminum.

## 7.3 Specific end use(s): Maintenance. For consumer, industrial and professional use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters:

The permitted average concentrations and permitted peak concentrations of dangerous substances in the air at the workplace and their characteristic properties according to Decree No. 5/2020 (II. 6.) ITM on the Protection of the Health and Safety of Workers from the Risks Related to Chemical Pathological Factors (Hungary):

Substance	CAS Number	ÁK-value mg/m <sup>3</sup>	CK-value mg/m <sup>3</sup>	Characteristics	Reference	ÁK correction group
ETHYL ALCOHOL	64-17-5	1900	3800	-	-	N
ISOPROPYL ALCOHOL	67-63-0	500	1000	b, i	-	R
n-BUTANE	106-97-8	2350	9400			N
1,3-BUTADIENE	106-99-0	2,2		k(1A), i	EU6	T
n-HEXANE	110-54-3	72		b, i, BEM	EU2	T

**N** Irritants, simple asphyxiants, low health hazards. Correction is NOT necessary.

**R** Substances whose health-damaging effect occurs as a result of SHORT exposure. Corrected  $\text{ÁK} = \text{ÁK} \times 8/\text{a number of hours per day}$

**T** Substances that have a harmful effect on health after LONG-TERM exposure. Corrected  $\text{ÁK} = \text{ÁK} \times 40/\text{hours per week}$ .

**i** Irritant substance that irritates the skin, mucous membranes, eyes, or all three.

**b** It is also absorbed through the skin.

**k(...)** Carcinogenic (classification according to the European Parliament and Council Regulation 1272/2008/EC, under another name: CLP Regulation).

**EU2** Value stated in Directive 2006/15/EC

**EU6** Value stated in EU Directive 2019/130

**BEM** Biological Exposure Indices.

**ÁK-value** Permitted average concentration.

**CK-value** Permitted peak concentration.

**CAS number** Chemical Abstracts Service registration number used to identify chemical substances.

Recommended limit values of biological exposure and effect indicators in urine for occupational chemical exposure in Hungary:

Chemical substance	Biological exposure (effect) indicator	Sampling time	mg/g creatinine	micromol/mmol creatinine (rounded values)	mg/l	µmol/l
n-HEXANE	2,5-hexanedione (after hydrolysis)	end of shift	-	-	2	18

**DNEL values:** No data available.

Data for ethyl alcohol:

Acute inhalation: 1900 mg/m<sup>3</sup> Worker, 950 mg/m<sup>3</sup> Consumer

Chronic, oral: 87 mg/kg/day Consumer

Chronic, transdermal: 343 mg/kg/day Worker, 206 mg/kg/day Consumer

Chronic, inhalation: 950 mg/m<sup>3</sup> Worker, 114 mg/m<sup>3</sup> Consumer

Data for ethyl alcohol:

Fresh water: 0.96 mg/l

Freshwater sediment: 3.6 mg/kg sediment dry material

Seawater: 0.79 mg/l

Wastewater treatment microorganisms: 580 mg/l

Soil (agriculture): 0.63 mg/kg soil dry material

## 8.2 Exposure controls:

According to Regulation 5/2020. (II. 6.) ITM: In the case of a hazardous substance not regulated by a limit value, the employer is obliged to reduce the level of exposure to the lowest level expected according to the scientific and technical standard, at which level, according to the current state of science, the hazardous substance has no health-damaging effect.

### Appropriate engineering controls:

The product must be used in a well-ventilated room.

### Individual protection measures, such as personal protective equipment:

#### Eye/Face protection:

Safety glasses with side shields/face shields are required if there is a risk of the mixture getting into the eyes.

#### Skin protection:

Protective gloves. Neoprene, nitrile rubber, viton. Penetration time: >480 minutes, EN-374-3

Protective clothing is required if direct contact or splashing may occur.

#### Respiratory protection:

In the event of vapour formation, the use of a respirator with a type "A" filter is justified.

In case of formation of vapours or aerosols: a gas mask with an "A/P2" combined filter is required.



Thermal hazards:

Not known.

Other precautions:

Keep away from food, drink and feed.

Hands must be washed after working hours and before breaks.

Environmental exposure controls

The product and waste from it must be prevented from entering living water, soil and public sewers. Local, national and waste water regulations must be complied with.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties:**

- |    |   |   |
|----|---|---|
| a) | Physical state:   | Aerosol   |
| b) | Colour:   | Colourless-yellowish  |
| c) | Odour:  | Characteristic  |
|    | Odour threshold:  | No data available.  |
| d) | Melting point/freezing point:                             | No data is available for the product.<br>Data for denatured alcohol: -114 °C<br>PB 4.2 T data: -187,6 °C - -138,3 °C                                |
| e) | Boiling point or initial boiling point and boiling range: | No data is available for the product.<br>Data for denatured alcohol: 78 °C<br>PB 4.2 T data: -104 – -60 °C  |
| f) | Flammability:   | Highly flammable aerosol.   |
| g) | Lower and upper explosion limit:                          | No data is available for the product.<br>Data for denatured alcohol:<br>lower: 3.5 vol%, upper: 15.0 vol%   |
| h) | Flash point:  | No data is available for the product.<br>Data for denatured alcohol: 12-14 °C   |
| i) | Auto-ignition temperature:                                | No data available.<br>PB 4.2 T data: 287 °C -537 °C   |
| j) | Decomposition temperature:                                | No data available.  |
| k) | pH:   | No data available.  |
| l) | Kinematic viscosity:                                      | No data available.  |
| m) | Solubility:   | Not applicable.<br>Denatured alcohol: Soluble in water.<br>PB 4.2 T data: 24.4-60.4 mg/l in water   |
| n) | Partition coefficient n-octanol/water (log value):        | No data available.  |
| o) | Vapour pressure:  | No data is available for the product.<br>PB 4.2 T data: ≤ 1600 kPa (70 °C)  |
| p) | Density and/or relative density:                          | No data is available for the product.<br>Denatured alcohol: 0.79-0.81 g/cm <sup>3</sup> (20 °C)<br>PB 4.2 T data: ≥ 0.505 g/cm <sup>3</sup> (50 °C) |
| q) | Relative vapour density:                                  | No data available.  |
| r) | Particle characteristics                                  | No data available.  |

**9.2 Other information:**

Explosive risk: Overpressure prevails in the device. Do not open, knock, puncture, expose to temperatures above 50°C, sunlight, radiant heat or throw into fire, even when empty! Do not spray on an open flame or glowing material. Refilling the device is prohibited! PB 4.2 T data: 5-15 vol% (literature data)



**SECTION 10: Stability and reactivity****10.1 Reactivity:** Not known.

Ethanol data: Reacts violently with strong oxidizing agents, strong reducing agents, acids, anhydrides, alkali metals, peroxides.

**10.2 Chemical stability:** Stable under normal use.**10.3 Possibility of hazardous reactions:** Product vapour can form an explosive mixture with air, which is heavier than air.

PB 4.2 T data: Contact with strong oxidizing agents (peroxides, chromates, etc.) can cause a fire hazard.

Information on denatured alcohol: Danger of explosion may occur during reaction with alkali metals, alkali oxides, acid anhydrides, silver nitrate, silver, nitric acid, silver nitrate/ammonia, silver oxide/ammonia.

**10.4 Conditions to avoid:** Keep away from heat, sources of ignition, hot surfaces, sparks, and open flames.**10.5 Incompatible materials:** Strong acids, oxidizing agents.

PB 4.2 T data: A mixture containing nitrates and other oxidizing agents (e.g. chlorates, perchlorates, liquid oxygen) can form an explosive mixture.

**10.6. Hazardous decomposition products:** In case of fire, toxic gases may be released (CO, CO<sub>2</sub>, hydrocarbons, aldehydes, soot).**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

- acute toxicity: Harmful if inhaled.

*Data on the ingredients of the product:*

PB 4.2 T data:

Propane: 1443 mg/l (inhalation, rat) (literature data)

n-Butane: 658 mg/l (inhalation, rat) (literature data)

Isobutane: 974 mg/l (inhalation, mouse) (literature data)

Data for isopropyl alcohol:

LD50: 5280 mg/kg (oral, rat)

LD50: 12800 mg/kg (dermal, rabbit)

Eye contact: irritation

Data for tert-butanol:

LD50: 2733 mg/kg (oral, rat)

LD50: >2000 mg/kg (dermal, rabbit)

Mild eye irritation.

- skin corrosion/irritation: Based on available data, the classification criteria are not met.
- serious eye damage/irritation: Causes serious eye irritation.
- respiratory or skin sensitisation: Based on available data, the classification criteria are not met.
- germ cell mutagenicity: Based on available data, the classification criteria are not met.
- carcinogenicity: Based on available data, the classification criteria are not met.

- reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: May cause respiratory irritation. Vapours may cause drowsiness or dizziness.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- aspiration hazard: Ingestion of the product is unlikely.

**11.2 Information on other hazards:** No data available.

Delayed and immediate effects from short and long-term exposure, as well as chronic effects: Due to lack of data, the classification criteria are not met.

Information on likely routes of exposure: Inhalation, skin contact, eye contact. Ingestion is unlikely.

## SECTION 12: Ecological information

**12.1 Toxicity:** The mixture must not be discharged into living water, public sewers or the ground. Harmful to aquatic life, causes long-term damage.

**Chronic toxicity:**

Data for denatured alcohol:

*Data for ethyl alcohol:*

LC50: 11200 mg/l (fish, 24 hours)

EC10/LC10 or NOEC freshwater invertebrates: 9.6 mg/l, 48 hours

EC10/LC10 or NOEC freshwater algae: 11.5 mg/l, 4 days

*Data for isopropyl alcohol:*

LC50: 9640 mg/l (fish, 96 hours)

EC50: 13299 mg/l (Daphnia magna, 48 hours)

EC5: >1000 mg/l (algae, 72 hours)

*Data for tert-butanol:*

LC50: 6410 mg/l (fish, 96 hours)

EC50: 933 mg/l (daphnia magna, 48 hours)

IC5: >1000 mg/l (algae, 72 hours)

PB 4.2 T data:

*Butane:* LC50: 24.11 mg/l (fish, literature data), LC50: 14.22 mg/l (other aquatic organisms, literature data)

EC50 96 hours: 7.71 mg/l (algae, literature data)

*Isobutane:* LC50: 27.98 mg/l (fish, literature data), LC50: 16.33 mg/l (other aquatic organisms, literature data)

EC50, 96 hours: 89.57 mg/l (algae, literature data)

*Propane:* LC50: 49.47 mg/l (fish, literature data), LC50: 27.14 mg/l (other aquatic organisms, literature data)

EC50, 72 hours: 11.89 mg/l (algae, literature data)

**12.2 Persistence and degradability:** No data are available for this product.

Denatured alcohol: Degradable immediately.

**12.3 Bioaccumulative potential:** No data are available for this product.

Data for ethyl alcohol:

Log KOW: -0.35, BCF: 3.2



PB 4.2 T data:

Log Kow: propane: 1.09-2.8 (literature data)

Log Kow: butane: 1.09- 2.8 (literature data)

Log Kow: isobutane: 1.09-2.8 (literature data)

**12.4 Mobility in soil:** No data available.**12.5 Results of PBT and vPvB assessment:** No data available.**12.6 Endocrine disrupting properties:** No data available.**12.7 Other adverse effects:** No data available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods:**

Disposal of the substance/mixture: It may be disposed of in accordance with local regulations. [225/2015. (VIII. 7.) Government Decree on the detailed rules of certain activities related to hazardous waste]

Disposal of contaminated packaging:

It may be disposed of in accordance with local regulations.

[442/2012. (XII. 29.) Government Decree on packaging and waste management activities related to packaging waste]

Recommended waste code: 16 05 04\* (gases containing dangerous substances stored in pressure-resistant containers (including halons).

The classification of this product into the appropriate waste identification main group, subgroup and individual waste types depends on the use of the material.

The wastes of the source resulting in the formation can be classified into several different main groups with regard to the properties of the given waste, taking into account the relevant regulations.

[72/2013. (VIII. 27.) VM decree on the waste list]

**SECTION 14: Transport information****14.1 UN number or ID number:** UN 1950**14.2 UN proper shipping name:** AEROSOLS, flammable**14.3 Transport hazard class(es):****ADR/RID:**

Class: 2

Classification code: 5F

Labels: 2.1

Transport category (Tunnel restriction code): 2 (D)

**14.4 Packing group:** Not applicable.**14.5 Environmental hazards:** Harmful to aquatic life with long lasting effects.**14.6 Special precautions for user:** Not applicable.**14.7 Maritime transport in bulk according to IMO instruments:** Not applicable.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:****Chemical safety:**

**COMMISSION REGULATION (EU) 2020/878** of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

**REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL** of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

**REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL** of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP)

**Act No. XXV. of 2000** on Chemical Safety

**Decree No. 44/2000 (XII.27.) EüM** on the detailed rules for certain procedures and activities related to dangerous substances and dangerous preparations

**Health and safety:**

**Decree No. 3/2002 (II.08.) SzCsM-EüM** concerning the minimum safety and health requirements of workplaces

**Act No. XCIII. of 1993** on occupational safety

**Decree No. 65/1999 (XII. 22.) EüM** on the minimal safety and health protection requirements regarding the utilization of individual protection tools by workers at the workplaces

**Decree No. 5/2020 (II. 6.) ITM** on the Protection of the Health and Safety of Workers from the Risks Related to Chemical Pathological Factors

**Waste management:**

**Act No. CLXXXV. of 2012** on Waste

**Governmental Decree No. 225/2015 (VIII. 7.)** on detailed rules of certain activities related to hazardous waste.

**Governmental Decree No. 442/2012 (XII. 29.)** on packaging and on waste management activities related to packaging waste

**Decree No. 72/2013 (VIII. 27.) VM** concerning the list of wastes

**Transport:**

**Decree No. 61/2013 (X. 17.) NFM** on the domestic application of Annexes A and B to the European Agreement Concerning the International Carriage of Dangerous Goods by Road (ADR)

**Other:**

**Decree No. 34/2014. (X. 30.) NGM** on the requirements for the distribution of aerosol products and aerosol packaging

**15.2. Chemical safety assessment:** The supplier has not carried out a chemical safety assessment.

**SECTION 16: Other information**

- a) This document is the first English version of the safety data sheet of Kontaktus tisztító. The English translation was based on version 8 of the Hungarian safety data sheet of the product dated 28 October 2022.
- b) Explanation of abbreviations and acronyms used in the safety data sheet:  
*CAS Number*: A number used to identify the chemical substance (Chemical Abstracts Service).  
*PBT substances*: Persistent, Bioaccumulative and Toxic substances.  
*vPvB substances*: very Persistent and very Bio-accumulative substances.  
*LD50*: The amount of a dose, given all at once, which causes the death of 50% of a group of test animals (Lethal Dose).  
*LC50*: The amount of a concentration, given all at once, which causes the death of 50% of a group of test animals (Lethal Concentration).  
*ADR*: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
*IMO*: International Maritime Organization.  
*RID*: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
*ICAO*: International Civil Aviation Organization.
- c) The hazard classification was carried out by the supplier according to the 1272/2008/EC: Application of interpolation principles based on the hazard classes of the components.
- d) The full text of the H sentences in Section 3 of the safety data sheet:
- H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
H340 May cause genetic defects.  
H350 May cause cancer.

The safety data sheet has been prepared in accordance with the applicable EU and Hungarian legislation in force. It is limited to our current knowledge, does not guarantee the properties of the product and does not form the basis of any legal relationship.

