

SAFETY DATA SHEET
IN ACCORDANCE WITH REGULATION (EC) 1907/2006 (REACH)
Tyre Conditioner Foam Spray

Preparing date: 13 January 2025

Version: 1.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier: Tyre Conditioner Foam Spray

UFI: YVYQ-4Q4H-SSKD-1C10

1.2 Relevant identified uses of the substance or mixture and uses advised against:
Identified uses: Maintenance

for consumer, professional and industrial use.

Uses advised against: Other than above.

1.3 Details of the supplier of the safety data sheet:
Distributor:

**Email address for a competent person
responsible for the safety data sheet:**

1.4 Emergency telephone number:

Health Toxicological Information Service, Hungary:

06-80-201-199 (free charge, 24 hours a day- from Hungary only)

06-1-476 6464 (Available 0-24 hours for a standard fee - also from abroad)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:
in accordance with Regulation (EC) No 1272/2008 (CLP)

Aerosols, Category 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

2.2 Label elements:

Dangerous substance(s) to be indicated: 40-45% propellant gas



Danger

Hazard Statement(s):

H222 Extremely flammable aerosol
H229 Pressurised container: May burst if heated.

Precautionary Statement(s):

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 F INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/ container: as hazardous waste.

Supplemental Hazard Information

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3 Other hazards:

Results of the PBT and vPvB assessment: Does not meet the criteria for PBT or vPvB substances.

Endocrine disrupting properties: No data available.

SECTION 3: Composition/information on ingredients**3.2 Mixtures:**

Substance	CAS Number	EC Number	Index Number/ REACH Registration Number	Concentration by weight	Classification in accordance with Regulation (EC) No 1272/2008
Poly(dimethylsiloxane) emulsion in water	polimer	-	-	-	* Acute Tox. 4, H302 Eye Dam. 1, H318
(isotridecanol, ethoxylated >3-<5%)	69011-36-5	-	-	-	
Propellant gas PB 4.2 T				40-45%	
Propane	74-98-6	200-827-9	601-003-00-5/01-2119486944-21		Flam.Gas 1, H220 Press Gas
Butane	106-97-8	203-448-7	601-004-00-0/01-2119474691-32		Flam.Gas 1, H220 Press Gas

Substance	CAS Number	EC Number	Index Number/ REACH Registration Number	Concentration by weight	Classification in accordance with Regulation (EC) No 1272/2008
Isobutane	75-28-5	200-857-2	601-004-0-0/01- 2119485395-27		Flam. Gas 1, H220 Press Gas
(1,3-butadiene content: < 0,1%)	106-99-0	203-450-8	601-013-00-X/01- 2119471988-16		Flam. Gas 1, H220 Press. Gas, H280 Muta. 1B, H340 Carc. 1A, H350

* Classification given by the manufacturer.

For the full text of H-sentences mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures:

Inhalation: (applies to propellant gas) The injured person should be taken to fresh air and given rest. In case of respiratory irritation (coughing) or breathing difficulties, call a doctor immediately. If breathing has stopped, a qualified person should start artificial respiration, or if the heart has stopped, cardiopulmonary resuscitation. Oxygen administration may be beneficial if given by a qualified person, preferably on medical advice.

Skin contact: (applies to propellant gas) Clothing contaminated or soaked with the product should be removed immediately. The affected skin should be washed with soap and water. Do not attempt to rewarm the affected skin on the site. Do not rub or apply dry heat. Carefully cut around the part of the cloth that is adhering to the wound. Cover the injured person loosely with sterile clothing. Get the injured person quickly to a first aid post or hospital.

Eye contact: (applies to propellant gas) The eyes should be rinsed thoroughly with plenty of running water for at least 15 minutes (with the eyelids pulled apart). Contact lenses should be removed if they are present and this can be easily done. Do not attempt to rewarm it. Cover both eyes with sterile cloths and the eye should be shown to a doctor.

Ingestion: The product is sold in aerosol cylinders, so ingestion is unlikely. In case of accidental spillage, the injured person should not be made to vomit and medical attention should be obtained.

4.2 Most important symptoms and effects, both acute and delayed:

Propellant gas: In high concentrations, it is asphyxiating, can cause asphyxiation, and the lack of oxygen can have fatal consequences.

4.3 Indication of any immediate medical attention and special treatment needed:

Show the safety data sheet or label to the doctor if possible. It should be treated symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Extinguishing powder, carbon dioxide (CO₂), alcohol-resistant extinguishing foam, water spray.

Unsuitable extinguishing agent: High pressure water jet. It should only be used to cool the bottles.

5.2 Special hazards arising from the substance or mixture:

The area must be cleared. The fire should only be extinguished from a safe distance or from a sheltered place. Avoid inhaling dangerous fumes and toxic decomposition products (approach from the wind). The best method for extinguishing flammable gas fires is to stop the gas flow before starting the extinguish. Due to the aerosol formulation, large spillage of the mixture is unlikely. The heat of the fire can cause a rapid build-up of pressure inside the cylinder and the cylinder may explode. Personnel and any materials not yet consumed by the fire should be moved to safety.

Hazardous combustion products: in case of fire, toxic gases may be released: CO, CO₂.

5.3 Advice for firefighters:

Full fire-resistant protective equipment. In the event of fire, breathing apparatus independent of ambient air must be worn.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

For persons not trained for an emergency:

Persons not trained for emergency situations should be kept away.

For persons trained for emergency situations:

Unauthorised persons must be kept away.

Ignition sources must be removed.

Ensure adequate ventilation.

Avoid contact with skin or eyes.

The vapour/spray of the product must not be inhaled.

Wear full protective clothing and breathing apparatus independent of ambient air.

6.2 Environmental precautions:

The product should not be released into drains or waterways.

Due to the small aerosol formulation, large spillage is unlikely.

If the spillage (propellant) enters the sewer system, there may be an explosion hazard.

All deeper and distant ignition sources should be eliminated.

6.3 Methods and material for containment and cleaning up:

Eliminate leaks if this can be done without danger.

Use water spray to reduce the concentration of the gas.

Close off the area until the gas dissipates.

Dispose of in accordance with regulations.

Only non-sparking equipment should be used.

Liquid residues should be collected with absorbent non-combustible material (dry earth, sand, etc.) and collected until disposal.

6.4 Reference to other sections:

Safe handling: see Section 7.

Personal protective equipment: see Section 8.

Waste treatment, disposal: see Section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling:**

Use only in well-ventilated areas! Keep away from heat and sources of ignition. Rules for pressurised containers must be followed. Avoid inhalation, contact with skin and eyes and ingestion of the mixture spray. Use a non-sparking ventilation system, explosion-proof equipment and an electrical system with internal safety. Always shake thoroughly before use. The appliance is overpressurised. Do not open, strike, puncture, expose to temperatures above 50°C, sunlight, radiant heat or throw into a fire, even when empty. Do not spray into an open flame or onto glowing material. Refilling the device is prohibited.

7.2 Conditions for safe storage, including any incompatibilities:

Specific storage requirements: adequate ventilation must be ensured.

Prevent electrostatic charging

Store in a dry, cool place at a temperature below 35°C.

Protect against freezing.

Keep away from heat and sources of ignition.

Keep out of the reach of children and away from food.

Incompatible substances: strong oxidising agents (e.g. perchlorates).

7.3 Specific end use(s): Maintenance for consumer, professional and industrial use.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters:**

The permitted average concentrations and permitted peak concentrations of dangerous substances in the air at the workplace and their characteristic properties according to Decree No. 5/2020 (II. 6.) ITM on the Protection of the Health and Safety of Workers from the Risks Related to Chemical Pathological Factors (Hungary):

Substance	CAS Number	ÁK-value mg/m ³	CK-value mg/m ³	Characteristics	Reference	ÁK correction group
n-BUTANE	106-97-8	2350	9400	-	-	N
1,3-BUTADIENE	106-99-0	2,2	-	k(1A), i	EU6	T

N Irritants, simple asphyxiants, low health hazards substances. Correction is NOT necessary.

T Substances that may cause adverse health effects CONSIDERING exposure after exposure. Corrected ÁK = ÁK x 40/a hours per week.

i An irritant that excites the skin, mucous membranes, eyes or all three

k(...) carcinogenic (classification in brackets according to Regulation (EC) No 1272/2008 of the European Parliament and of the Council, CLP Regulation for short)

EU6 Value published in EU Directive 2019/130

ÁK-value Permitted average concentration.

CK-value Permitted peak concentration.

CAS number Chemical Abstracts Service registration number used to identify chemical substances.

DNELs, PNECs: No data available for the mixture.

8.2 Exposure controls:

According to Decree No. 5/2020 (II. 6.) ITM on the Protection of the Health and Safety of Workers from the Risks Related to Chemical Pathological Factors (Hungary):

In the case of a dangerous substance not regulated by a limit value, the employer must reduce the level of exposure to the lowest level that can be expected according to the state of scientific and technical knowledge, at which level the dangerous substance has no harmful effects on health.

Technical measures: the product should be used in a well-ventilated area with spark-free equipment.

Individual precautions, such as personal protective equipment:

Eye protection: Wear protective goggles/face shields if there is a risk of eye contact with the mixture.

Skin protection:

Hand protection: Protective gloves (nitrile rubber, butyl rubber).

Wear protective clothing if direct contact or splashing may occur.

Respiratory protection: Adequate non-sparking ventilation (general ventilation, local exhaust ventilation) is required. Where exposure above the permissible limit value may occur in the workplace air, respiratory protection should be used.

Thermal hazard: not known.

Other precautions: keep away from food, drink and animal feed.

Wash hands after working hours and before breaks.

Environmental exposure controls:

Product and its waste must be prevented from entering living water, soil and drains. Local, national and waste water regulations must be fulfilled.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

- | | | |
|----|--|---|
| a) | Physical State: | Aerosol |
| b) | Colour: | Colourless |
| c) | Odour: | Odourless |
| | odour threshold | No data available. |
| d) | Melting point/freezing point | No data available. |
| | | <i>PB 4.2 T data</i> : -187,6÷ -138,3°C |
| | | <i>Silicone emulsion data</i> : -1°C |
| e) | Boiling point or initial boiling point and boiling range | No data available. |
| | | <i>PB 4.2 T data</i> : -104÷ -60°C |

f)	Flammability	Highly flammable aerosol. The device is overpressurised. Do not open, bang, prick, expose to temperatures above 50°C, sunlight, radiant heat or throw into a fire, even when empty! Do not spray into an open flame or onto glowing material. Refilling the device is prohibited! <i>PB 4.2 T data: 5-15 V/V% (literature data)</i>
g)	Lower and upper explosion limit	No data available for the mixture.
h)	Flash point	No data available for the mixture.
i)	Auto-ignition temperature	No data available for the mixture. <i>PB 4.2 T data: 287-537°C</i>
j)	Decomposition temperature	No data available for the mixture. <i>Silicone emulsion data: >150°C</i>
k)	pH	No data available for the mixture. <i>Silicone emulsion data: 3-7 (25°C)</i>
l)	Kinematic viscosity	No data available for the mixture. <i>Silicone emulsion data: 10-30 mPa s (dynamic)</i>
m)	Solubility	The mixture is not miscible with water. <i>PB 4.2 T data: 24,4-60,4 mg/l in water</i>
n)	Partition coefficient n-octanol/water (log value)	No data available.
o)	Vapour pressure	No data available for the mixture. <i>PB 4.2 T data: ≤1600 kPa (70°C)</i> <i>Silicone emulsion data: 23 hPa (20°C)</i>
p)	Density and/or relative density	No data available for the mixture <i>PB 4.2 T data: ≥ 0,505 g/cm³ (50°C)</i>
q)	Relative vapour density (20°C)	No data available. <i>PB 4.2 T data: ≤1600 kPa (70°C)</i>
r)	Particle characteristics	No data available.

9.2 Other information:

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity:** No data available for the mixture.**10.2 Chemical stability:** Stable under normal use.**10.3 Possibility of hazardous reactions:** No data available for the mixture.*PB 4.2 T data:* Contact with strong oxidizing agents (peroxides, chromates, etc.) may cause a fire hazard.

- 10.4 Conditions to avoid:** Keep away from heat, ignition sources, hot surfaces, sparks and open flames.
- 10.5 Incompatible materials:** Strong acids, oxidizing agents.
PB 4.2 T data: Mixtures containing nitrates and other oxidizing agents (e.g. chlorates, perchlorates, liquid oxygen) may form an explosive mixture.
- 10.6 Hazardous decomposition products:** In case of fire, toxic gases may be released: CO, CO₂, silicon oxides, imperfectly burnt hydrocarbons.
Silicone emulsion data: (Refers to the silicone part of the mixture) According to measurements from about 150°C small amount of formaldehyde is released through oxidative decomposition.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

- Acute toxicity: Based on available data, the classification criteria are not met.

PB 4.2 T

Propane: LC50 1443 mg/l (inhaled, rat) (literature data)

n-Butane: LC50 658 mg/l (inhaled, rat) (literature data)

Isobutane: LC50 974 mg/l (inhaled, mouse) (literature data)

Silicone emulsion data: LD50 >2000 mg/kg (oral, rat)

LD50 >2000 mg/kg (dermal, rat)

- Skin corrosion/irritation: Based on available data, the classification criteria are not met.
- Serious eye damage/irritation: Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
The mutagenicity of the substance has been extensively tested in in-vivo and in-vitro studies
Genetic toxicity: negative
- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- Aspiration hazard: Based on available data, the classification criteria are not met.

Information on likely routes of exposure:

Inhalation, skin contact, eye contact. Ingestion unlikely.

11.2 Information on other hazards:

No data available for the mixture.

SECTION 12: Ecological information**12.1 Toxicity:** No data available for the mixture.

The mixture should not be released into living water, public sewers or soil.

PB 4.2 T

Butane: LC50: 24,11 mg/l (fish, literature data), LC50: 14,22 mg/l (other aquatic organisms, literature data)

EC50 96 h: 7,71 mg/l (algae, literature data)

isobutane: LC50: 27,98 mg/l (fish, literature data), LC50: 16,33 mg/l (other aquatic organisms, literature data)

EC50, 96 h: 89,57 mg/l (algae, literature data)

Propane: LC50: 49,47 mg/l (fish, literature data), LC50: 27,14 mg/l (other aquatic organisms, literature data)

EC50, 72 h: 11,89 mg/l (alga, literature data)

Silicone emulsion data: LC50: >100 mg/l (Danio rerio, 96 h)

EC50: >100 mg/l (Daphnia magna, 48 h)

EC50: >1000 mg/l (sludge, 3 h)

12.2 Persistence and degradability: No data are available on the mixture.**12.3 Bioaccumulative potential:** No data are available on the mixture.

PB 4.2 T data:

Log Kow: propane: 1,09-2,8 (literature data)

Log Kow: butane: 1,09- 2,8 (literature data)

Log Kow: isobutane: 1,09-2,8 (literature data)

12.4 Mobility in soil: No data available.**12.5 Results of PBT and vPvB assessment:** No data available.**12.6 Endocrine disrupting properties:** No data available.**12.7 Other adverse effects:** No data available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods:**

Disposal of the substance/mixture:

Disposal should be carried out in compliance with local regulations.

[Government Decree 225/2015 (VIII. 7.) on the detailed rules for certain activities involving hazardous waste, Hungarian legislation]

Disposal of contaminated packaging:

Disposal subject to local regulations.

[Government Decree 442/2012 (XII. 29.) on packaging and packaging waste management activities, Hungarian legislation]

Waste identification code: 16 05 04* hazardous waste stored in pressure vessels gases (including halons) containing dangerous substances

This product is assigned to the appropriate waste identification major group, subgroup and each depends on the use of the material.

Waste from the generating source may be classified in several different main groups according to the characteristics of the waste, taking into account the relevant regulations. [Decree 72/2013 (VIII. 27.) VM on the list of waste, Hungarian legislation]

SECTION 14: Transport information

- 14.1 UN number or ID number:** UN 1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):**
 Class: 2
 Classification code: 5F
 Labels: 2.1
 Transport category (Tunnel restriction code): 2 (D)
- 14.4 Packing group:** -
- 14.5 Environmental hazards:** -
- 14.6 Special precautions for user:** Not applicable.
- 14.7 Maritime transport in bulk according to IMO instruments:** Not applicable.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Chemical safety:

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP)

Act No. XXV. of 2000 on Chemical Safety (Hungarian legislation)

Decree No. 44/2000 (XII.27.) EüM on the detailed rules for certain procedures and activities related to dangerous substances and dangerous preparations (Hungarian legislation)

34/2014. (X. 30.) NGM Regulation on the marketing requirements for aerosol products and aerosol packaging

Health and safety:

Decree No. 3/2002 (II.08.) SzCsM-EüM concerning the minimum safety and health requirements of workplaces (Hungarian legislation)

Act No. XCIII. of 1993 on occupational safety (Hungarian legislation)

Decree No. 65/1999 (XII. 22.) EüM on the minimal safety and health protection requirements regarding the utilization of individual protection tools by workers at the workplaces (Hungarian legislation)

Decree No. 5/2020 (II. 6.) ITM on the Protection of the Health and Safety of Workers from the Risks Related to Chemical Pathological Factors (Hungarian legislation)

Fire safety:

Decree No. 54/2014 (XII. 5.) BM on the National Fire Safety Codes (Hungarian legislation)
Act No. XXXI. of 1996 on fire prevention, technical rescue and the fire department (Hungarian legislation)

Waste management:

Act No. CLXXXV. of 2012 on Waste (Hungarian legislation)
Governmental Decree No. 225/2015 (VIII. 7.) on detailed rules of certain activities related to hazardous waste. (Hungarian legislation)
Governmental Decree No. 442/2012 (XII. 29.) on packaging and on waste management activities related to packaging waste (Hungarian legislation)
Decree No. 72/2013 (VIII. 27.) VM concerning the list of wastes (Hungarian legislation)

Transport:

Decree No. 61/2013 (X. 17.) NFM on the domestic application of Annexes A and B to the European Agreement Concerning the International Carriage of Dangerous Goods by Road (ADR), (Hungarian legislation)

Other:

REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents

15.2. Chemical safety assessment: No data available.

SECTION 16: Other information

- a) This document is the first English version of the safety data sheet of the product. The English translation was based on version 7 of the Hungarian safety data sheet of the product dated 08.06.2022.
- b) Explanation of abbreviations and acronyms used in the safety data sheet:
BCF: Bioconcentration Factor is an indicator of a chemical substance's tendency to accumulate in the living organism. It can be obtained by calculation method based on logPow or bio-accumulation test.
PBT substances: Persistent, Bioaccumulative and Toxic substances.
vPvB substances: very Persistent and very Bio-accumulative substances.
LD50: The amount of a dose, given all at once, which causes the death of 50% of a group of test animals (Lethal Dose).
LC50: The amount of a concentration, given all at once, which causes the death of 50% of a group of test animals (Lethal Concentration).
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
IMO: International Maritime Organization.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
ICAO: International Civil Aviation Organization.
- c) The hazard classification was carried out by the supplier according to the 1272/2008/EC, based on calculation method.
- d) The full text of the H sentences in Section 3 of the safety data sheet:
- H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated

H280 Contains gas under pressure; may explode if heated
H340 May cause genetic defects.
H350 May cause cancer.
H302 Harmful if swallowed.
H318 Causes serious eye damage.

The safety data sheet has been prepared in accordance with the applicable EU and Hungarian legislation in force. It is limited to our current knowledge, does not guarantee the properties of the product and does not form the basis of any legal relationship.